IMMERSION BLENDERS

robot of coupe[®]

MP 350 Ultra Combi



A

B

SALES DESCRIPTION

Ideal for blending soups and puréeing fruit and vegetables. Special institutional catering model intended for intensive use. In its Combi version, the whisk function can be used for mashed potato and pancake batter.

TECHNICAL DESCRIPTION

MP 350 Ultra Combi immersion blender. Single phase. Power: 440 W. Variable speed: 1,500 - 9,000 rpm (blender function) and 250 1,500 rpm (whisk function). 100% stainless-steel blades, bell and tube (total length: 350 mm). "EasyPlug" system with detachable power cord

C TECHNICAL DATA	
440 W	
Single phase - Plu	ug supplied
1,500 - 9,000 rpm (blender function) 250 - 1,500 rpm (whisk function)	
95%	
5.9 kg	
Amperage	Reference
2.1 Amp	34860L
g 2.1 Amp	34861L
3.7 Amp	34865L
2.1 Amp	34868L
	440 W Single phase - Plu 1,500 - 9,000 rp 250 - 1,500 rpm 95% 5.9 kg Amperage 2.1 Amp 2.1 Amp 3.7 Amp

STANDARDS

EN 12100-1 & 2-2004, EN 60204-1-2006, EN 12853, EN 60529-2000 : IP55 & IP34



CHARACTERISTICS AND BENEFITS

MOTOR UNIT

E

- Power 440 W
- Stainless-steel motor unit with air vents in the top section only to ensure watertightness
- Lug on motor housing serves as a rest and pivot on the pan rim for greater user comfort
- Variable speed 1,500 9,000 rpm (blender function) and 250 1,500 rpm (whisk function)
- Self-regulating speed system
- New patented "EasyPlug" system making it easier to replace the power cord during after-sales servicing
- Cord winding system for tidy storage and optimum lifespan

TUBE AND BELL

- 100% stainless-steel blades, bell and tube (total length: 350 mm)
- Foot with detachable bell and blades (patented system exclusive to Robot-Coupe)
- Watertight bell design for optimum lifespan
- Even sturdier all-metal housing for whisk attachment to cope with very thick mixtures

STANDARD ATTACHMENTS

- Wall-mounted immersion blender holder
- Tool for fixing and detaching the blades

IMMERSION BLENDERS

robot @ coupe°

MP 350 Ultra Combi

F

OPTIONAL ATTACHMENTS

- 3 adjustable stainless-steel pan supports:
 - Ref. 27363 for pans with a diameter of 330 650 mm
 - Ref. 27364 for pans with a diameter of 500 1000 mm
 - Ref. 27365 for pans with a diameter of 850 1300 mm
- 1 universal pan support:
 - Ref. 27358 screws onto pan rim





C DRAWINGS & DIMENSIONS Power cord and plug supplied 177 177 125 177 124 100 125 100 100 100 100 100 100 100 100 100 100 100 100

Specification sheet