

CMP 400 V.V.



Easy Plug




D

Pan capacity

up to 73 litres

▶ Special catering model



CMP

A

SALES DESCRIPTION

Ideal for blending soups and puréeing fruit and vegetables. Special catering model. Compact, efficient and easy to handle

B

TECHNICAL DESCRIPTION

CMP 400 V.V. Immersion Blender. Single phase. Power 420 W. Variable speed: 2,300 - 9,600 rpm. 100% stainless-steel blades, bell and tube (total length: 400 mm)

C

TECHNICAL DATA

Output power	420 W	
Electrical datas	Single phase - Plug supplied	
Variable speed	2,300 - 9,600 rpm	
Rate of recyclability	95%	
Net weight	3.6 kg	
Supply	Amperage	Reference
230V/50/1	1.9 Amp	34260B
240V/50/1 UK plug	1.9 Amp	34261B

E

CHARACTERISTICS AND BENEFITS

MOTOR UNIT

- Power 420 W
- Stainless-steel motor unit with air vents in the top section only to ensure watertightness
- Variable speed 2300 to 9600 rpm.
- Self-regulating speed system
- Variable speed for more elaborate tasks allowing for greater flexibility of use

TUBE AND BELL

- 100% stainless-steel blades, bell and tube (total length: 400 mm)
- Foot with detachable bell and blades (patented system exclusive to Robot-Coupe)

STANDARD ATTACHMENTS

- Wall-mounted immersion blender holder
- Tool for fixing and detaching the blades

STANDARDS

EN 12100-1 & 2-2004, EN 60204-1-2006, EN 12853, EN 60529-2000 : IP55 & IP34



CMP 400 V.V.

CMP 400 V.V.

G

DRAWINGS & DIMENSIONS

Power cord and plug supplied

