



- Electromechanical control panel.
- 1 washing cycle of 120".
- Tank capacity: 25 l./Heating power: 2.8 kW.
- Boiler capacity: 7 l./Heating power: 2.8 kW.
- Wash pump power: 0.6 kW.
- Rinsing consumption: 2.6 l/rinse.
- Upper and lower washing and rinsing arms.
- COLD models: Independent cycle for cold rinsing useful for cooling glasses immediately after washing.
- Stainless steel washing arms.
- Built-in rinse-aid dispenser.
- Anti backflow valve fitted.
- Safety thermostat in washing tank and boiler.
- Temperatures adjusted: wash 60 °C and rinse 85 °C.

- Supply voltage: 230 V 1N 50 Hz.
- Accessories supplied: 1 basket CP-16/18, 1 basket CT-10 and 1 basket for cutlery CU-7.

OPTIONAL MODELS WITH

- Built-in drain pump.
- Built-in electric rinse-aid dispenser.
- Built-in detergent dispenser.
- Wash tank stainless steel filter.
- Stainless steel rinsing arms.
- 60 Hz version.
- UK version with 2.2 kW boiler heating power, 2 kW tank heating power and UK plug (13 A).

Model	Reference	baskets / hour	Door clearance (mm)	Dimensions (mm)	Detergent dispenser	Drain pump	Cold rinsing	Power (kW)	Voltage (V)
GE-500	19047202	30	320	600 x 605 x 830	No	No	No	3.4	230V-1N-50Hz
GE-500 DD	19047938	30	320	600 x 605 x 830	Yes	No	No	3.4	230V-1N-50Hz
GE-500 B	19059577	30	320	600 x 600 x 820	No	Yes	No	3.4	230V-1N-50Hz
GE-500 B DD	19055860	30	320	600 x 605 x 830	Yes	Yes	No	3.4	230V-1N-50Hz
GE-500 COLD	19106457	30	320	600 x 605 x 830	No	No	Yes	3.4	230V-1N-50Hz
GE-500 COLD DD	19106459	30	320	600 x 605 x 830	Yes	No	Yes	3.4	230V-1N-50Hz
GE-500 COLD B	19106470	30	320	600 x 605 x 830	No	Yes	Yes	3.4	230V-1N-50Hz
GE-500 COLD B DD	19106458	30	320	600 x 605 x 830	Yes	Yes	Yes	3.4	230V-1N-50Hz