



- Electromechanical control panel.
- 2 washing cycles: 90"/180"
- Tank capacity: 25 l./Heating power: 2.8 kW.
- Boiler capacity: 7 l./Heating power:5.6 kW.
- Wash pump power: 0.6 kW.
- Rinsing consumption: 2.6 l/rinse.
- Upper and lower washing and rinsing arms.
- Stainless steel washing arms.
- Built-in rinse-aid dispenser.
- Anti-backflow valve fitted.
- Safety thermostat in washing tank and boiler.
- Temperature adjustment: wash 60 °C and rinse 85 °C.
- Multi-Voltage: 400 V 3N, 230 V 3~, 230 V 1N.
- Adjustable boiler heating power (Multi-Power): 2.8 kW/3.7 kW/5.6 kW.
- Accessories supplied: 1 basket CP-16/18, 1 basket CT-10 and 1 basket for cutlery CU-7.

OPTIONAL MODELS WITH

- Built-in drain pump.
- Built-in electric rinse-aid dispenser.
- Built-in detergent dispenser.
- Wash tank stainless steel filter.
- Stainless steel rinsing arms.
- 60 Hz version.
- UK version with 2 kW tank heating power, 5.6 kW in boiler heating power and 3x6 mm<sup>2</sup> power cord (230 V 1N, 30 A).

Model	Reference	Baskets/hour	Door clearance (mm)	Dimensions (mm)	Detergent dispenser	Drain pump	Power (kW)	Voltage (V)
GE-510	<b>19053414</b>	40	320	600 x 605 x 830	No	No	6.2	400V-3N-50Hz
GE-510 DD	<b>19059578</b>	40	320	600 x 605 x 830	Yes	No	6.2	400V-3N-50Hz
GE-510 B	<b>19059579</b>	40	320	600 x 605 x 830	No	Yes	6.2	400V-3N-50Hz
GE-510 B DD	<b>19059580</b>	40	320	600 x 605 x 830	Yes	Yes	6.2	400V-3N-50Hz