



600 Series

Fryers 600

**GAS FRYER, FG6-05**

**DIMENSIONS**

|         |    | <u>Article</u> | <u>Packed</u> |
|---------|----|----------------|---------------|
| Length  | mm | <b>400,00</b>  | <b>425,00</b> |
| Depth   | mm | <b>650,00</b>  | <b>675,00</b> |
| Height  | mm | <b>440,00</b>  | <b>500,00</b> |
| Weigth  | Kg | <b>18,00</b>   | <b>20,00</b>  |
| Volumen | m3 | <b>0,11</b>    | <b>0,16</b>   |

**ELECTRICITY**

|          |  |  |             |
|----------|--|--|-------------|
| Not used |  |  | <b>0,00</b> |
|----------|--|--|-------------|

**WATER**

Not used

**GAS**

|             |                    |                 |
|-------------|--------------------|-----------------|
| Power       | KW                 | <b>6,98</b>     |
|             | Kcal/h             | <b>6.002,80</b> |
| LPG         | Consumption (kg/h) | <b>0,55</b>     |
|             | Pressure (g/cm2)   | <b>37,00</b>    |
| Natural Gas | Consumption (m3/h) | <b>0,75</b>     |
|             | Pressure (g/cm2)   | <b>18,00</b>    |

**STEAM**

Not used

**AIR**

Not used

GAS FRYER, FG6-05

Made of stainless steel

Capacity: one 8 litre oil/well.

Tank equipment: 1 basket 220x240x100 mm .

Thermostat temperature control 60 °C to 195 °C.

Automatic burner ignition by means of an electromagnetic valve, with pilot light and thermocouple.

Safety thermostat.

Drainage tap.

Power: 6,000 Kcal/h. (7 KW).

Dimensions: 400 x 650 x 440 mm.

**Certificate EQNET- CE**

**Cgaz-1312BU5331**

| <b>Connections points</b> | <b>X</b> | <b>Y</b> | <b>Z</b> | <b>Diameter</b> | <b>Information</b>                           |
|---------------------------|----------|----------|----------|-----------------|----------------------------------------------|
| GAS                       | 312      | 492      | 105      | R.3/4"G         | Prever regulador y llave de corte individual |

